



Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
L90 / 50000 h
DALI-2, non DIM
front IP20

Types



Colours



Mounting set



Light distributions






UNICO L4 / L6

recessed

EN Rectangular recessed multi-downlight made of die-cast aluminium; equipped with four (L4) / six (L6) individually selectable or pre-specified, customised light elements; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering

DE Rechteckiger Einbau-Multi-Downlight aus Aluminiumdruckguss; bestückt mit vier (L4) / sechs (L6) individuell wählbaren oder fix definierten, anwendungsspezifischen Optiken; werkzeuglose Montage im Montageset durch Kugelschnappsystem; einfache elektrische Montage durch verpolungssichere Steckverbindung; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; Einbau in unterschiedlichen Gehäusen möglich; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; präzise Abstrahlcharakteristik mit unterschiedlichen symmetrischen Lichtverteilungen; oder mit asymmetrischer Lichtverteilung; energieeffiziente High-Power-LEDs mit sehr guter Farbwiedergabe



black & chrome reflector



one luminaire multiple scenes




up to 145 lm/W (high efficiency)



tunable white 2700 – 5000 K (optional)







UNICO L4



MEDIUM ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7L49 B0 41
	3000 K	lm	090-7L40 B0 41
	3500 K	lm	090-7L42 B0 41
	4000 K	lm	090-7L41 B0 41

FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7L49 C0 41
	3000 K	lm	090-7L40 C0 41
	3500 K	lm	090-7L42 C0 41
	4000 K	lm	090-7L41 C0 41

WIDE FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7L49 D0 41
	3000 K	lm	090-7L40 D0 41
	3500 K	lm	090-7L42 D0 41
	4000 K	lm	090-7L41 D0 41

SPOT ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7L49 K0 41
	3000 K	lm	090-7L40 K0 41
	3500 K	lm	090-7L42 K0 41
	4000 K	lm	090-7L41 K0 41

MEDIUM SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7L49 E0 41
	3000 K	lm	090-7L40 E0 41
	3500 K	lm	090-7L42 E0 41
	4000 K	lm	090-7L41 E0 41

FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7L49 F0 41
	3000 K	lm	090-7L40 F0 41
	3500 K	lm	090-7L42 F0 41
	4000 K	lm	090-7L41 F0 41

Order options

CONTROL		COLOUR	
non DIM	1	chrome reflector	0
DALI-2	3	black reflector	B

WIDE FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	0 9 0 - 7 L 4 9 ◆ G 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 L 4 0 ◆ G 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 L 4 2 ◆ G 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 L 4 1 ◆ G 0 ◪ 4 1


WALLWASHER chrome reflector, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	1140 lm	0 9 0 - 7 L 4 9 ◆ A 0 0 4 1
	3000 K	1140 lm	0 9 0 - 7 L 4 0 ◆ A 0 0 4 1
	3500 K	1190 lm	0 9 0 - 7 L 4 2 ◆ A 0 0 4 1
	4000 K	1210 lm	0 9 0 - 7 L 4 1 ◆ A 0 0 4 1

WALL FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	1340 lm	0 9 0 - 7 L 4 9 ◆ W 0 ◪ 4 2
	3000 K	1340 lm	0 9 0 - 7 L 4 0 ◆ W 0 ◪ 4 2
	3500 K	1400 lm	0 9 0 - 7 L 4 2 ◆ W 0 ◪ 4 2
	4000 K	1430 lm	0 9 0 - 7 L 4 1 ◆ W 0 ◪ 4 2





UNICO L6

CRI ≥ 90 · 2 SDCM · 1 ADDR. · X-PERT · X-PERT

MEDIUM ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	0 9 0 - 7 L 6 9 ◆ B 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 L 6 0 ◆ B 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 L 6 2 ◆ B 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 L 6 1 ◆ B 0 ◪ 4 1

FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	0 9 0 - 7 L 6 9 ◆ C 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 L 6 0 ◆ C 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 L 6 2 ◆ C 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 L 6 1 ◆ C 0 ◪ 4 1

WIDE FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	0 9 0 - 7 L 6 9 ◆ D 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 L 6 0 ◆ D 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 L 6 2 ◆ D 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 L 6 1 ◆ D 0 ◪ 4 1

Order options

CONTROL ◆		COLOUR ◪		COLOUR	
non DIM	1	chrome reflector	0	jet black	RAL 9005
DALI-2	3	black reflector	B	traffic white	RAL 9016

SPOT ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	090-7L69 ⇕ K0 ◪ 41
	3000 K	lm	090-7L60 ⇕ K0 ◪ 41
	3500 K	lm	090-7L62 ⇕ K0 ◪ 41
	4000 K	lm	090-7L61 ⇕ K0 ◪ 41

MEDIUM SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	090-7L69 ⇕ E0 ◪ 41
	3000 K	lm	090-7L60 ⇕ E0 ◪ 41
	3500 K	lm	090-7L62 ⇕ E0 ◪ 41
	4000 K	lm	090-7L61 ⇕ E0 ◪ 41

FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	090-7L69 ⇕ F0 ◪ 41
	3000 K	lm	090-7L60 ⇕ F0 ◪ 41
	3500 K	lm	090-7L62 ⇕ F0 ◪ 41
	4000 K	lm	090-7L61 ⇕ F0 ◪ 41

WIDE FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	090-7L69 ⇕ G0 ◪ 41
	3000 K	lm	090-7L60 ⇕ G0 ◪ 41
	3500 K	lm	090-7L62 ⇕ G0 ◪ 41
	4000 K	lm	090-7L61 ⇕ G0 ◪ 41

RECTANGULAR MEDIUM CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	090-7L69 ⇕ R0 ◪ 41
	3000 K	lm	090-7L60 ⇕ R0 ◪ 41
	3500 K	lm	090-7L62 ⇕ R0 ◪ 41
	4000 K	lm	090-7L61 ⇕ R0 ◪ 41

WALLWASHER chrome reflector, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	1710 lm	090-7L69 ⇕ A0041
	3000 K	1710 lm	090-7L60 ⇕ A0041
	3500 K	1780 lm	090-7L62 ⇕ A0041
	4000 K	1820 lm	090-7L61 ⇕ A0041

Order options

CONTROL	⇕
non DIM	1
DALI-2	3


COLOUR	◪
chrome reflector	0
black reflector	B

COLOUR	
jet black	RAL 9005
traffic white	RAL 9016

WALL FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	2010 lm	0 9 0 - 7 L 6 9 ⇕ W 0 ◪ 4 1
	3000 K	2010 lm	0 9 0 - 7 L 6 0 ⇕ W 0 ◪ 4 1
	3500 K	2100 lm	0 9 0 - 7 L 6 2 ⇕ W 0 ◪ 4 1
	4000 K	2140 lm	0 9 0 - 7 L 6 1 ⇕ W 0 ◪ 4 1

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready


Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS	L·W·H (mm)	ORDER CODE
12.5/15/20/25 mm	160·47·47	0 9 0 - 7 L 4 0 1 0 0


for UNICO L4



MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS	L·W·H (mm)	ORDER CODE
12.5/15/20/25 mm	235·47·47	0 9 0 - 7 L 6 0 1 0 0


for UNICO L6



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
jet black	176·63·30	0 9 0 - 7 L 4 0 2 0 B
traffic white	176·63·30	0 9 0 - 7 L 4 0 2 0 W

for UNICO L4



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
jet black	251·63·30	0 9 0 - 7 L 6 0 2 0 B
traffic white	251·63·30	0 9 0 - 7 L 6 0 2 0 W

for UNICO L6

Mounting tools accessories (optional)


DISMOUNTING TOOL

L·W·H (mm)	ORDER CODE
70·30·2	0 9 0 - 0 0 2 1 0 0

Order options

CONTROL	⇕	COLOUR	◪	COLOUR	
non DIM	1	chrome reflector	0	jet black	RAL 9005
DALI-2	3	black reflector	B	traffic white	RAL 9016

Electrical accessories (optional)



POWER SUPPLY pre-wired

Available in the configurator

see POWER SUPPLY PRE-WIRED

Gasthaus Vilsalpsee, Tannheim

Austria

Architect
Mario Gasser
Architecture

Photographer
Christian Flatscher




Used products



SASSO 60 round wall



UNICO L4 / L6 recessed



SASSO 60 round downlight recessed 1 lamp

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com







