

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
L90 / 50000 h
DALI-2, non DIM
front IP20

Types



Colours



Mounting set



Light distributions






UNICO Q9

recessed

EN Square recessed multi-downlight made of die-cast aluminium; equipped with nine individually selectable or pre-specified, customised light elements; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering

DE Quadratischer Einbau-Multi-Downlight aus Aluminiumdruckguss; bestückt mit neun individuell wählbaren oder fix definierten, anwendungsspezifischen Optiken; werkzeuglose Montage im Montageset durch Kugelschnappsystem; einfache elektrische Montage durch verpolungssichere Steckverbindung; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; Einbau in unterschiedlichen Gehäusen möglich; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; präzise Abstrahlcharakteristik mit unterschiedlichen symmetrischen Lichtverteilungen; oder mit asymmetrischer Lichtverteilung; energieeffiziente High-Power-LEDs mit sehr guter Farbwiedergabe



black & chrome reflector



one luminaire multiple scenes




up to 145 lm/W (high efficiency)



tunable white 2700 – 5000 K (optional)







UNICO Q9

CRI ≥ 90 · 2 SDCM · 1 ADDR. · X-PERT · X-PERT

MEDIUM ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	090 - 7Q99 ⇕ B0◪41
	3000 K	lm	090 - 7Q90 ⇕ B0◪41
	3500 K	lm	090 - 7Q92 ⇕ B0◪41
	4000 K	lm	090 - 7Q91 ⇕ B0◪41

FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	090 - 7Q99 ⇕ C0◪41
	3000 K	lm	090 - 7Q90 ⇕ C0◪41
	3500 K	lm	090 - 7Q92 ⇕ C0◪41
	4000 K	lm	090 - 7Q91 ⇕ C0◪41

WIDE FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	090 - 7Q99 ⇕ D0◪41
	3000 K	lm	090 - 7Q90 ⇕ D0◪41
	3500 K	lm	090 - 7Q92 ⇕ D0◪41
	4000 K	lm	090 - 7Q91 ⇕ D0◪41

SPOT ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	090 - 7Q99 ⇕ K0◪41
	3000 K	lm	090 - 7Q90 ⇕ K0◪41
	3500 K	lm	090 - 7Q92 ⇕ K0◪41
	4000 K	lm	090 - 7Q91 ⇕ K0◪41

MEDIUM SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	090 - 7Q99 ⇕ E0◪41
	3000 K	lm	090 - 7Q90 ⇕ E0◪41
	3500 K	lm	090 - 7Q92 ⇕ E0◪41
	4000 K	lm	090 - 7Q91 ⇕ E0◪41

FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	090 - 7Q99 ⇕ F0◪41
	3000 K	lm	090 - 7Q90 ⇕ F0◪41
	3500 K	lm	090 - 7Q92 ⇕ F0◪41
	4000 K	lm	090 - 7Q91 ⇕ F0◪41

Order options

CONTROL ⇕		COLOUR ◪	
non DIM	1	chrome reflector	0
DALI-2	3	black reflector	B

WIDE FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	0 9 0 - 7 Q 9 9 ⇕ G 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 9 0 ⇕ G 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 9 2 ⇕ G 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 9 1 ⇕ G 0 ◪ 4 1


WALLWASHER chrome reflector, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	2660 lm	0 9 0 - 7 Q 9 9 ⇕ A 0 0 4 1
	3000 K	2660 lm	0 9 0 - 7 Q 9 0 ⇕ A 0 0 4 1
	3500 K	2770 lm	0 9 0 - 7 Q 9 2 ⇕ A 0 0 4 1
	4000 K	2830 lm	0 9 0 - 7 Q 9 1 ⇕ A 0 0 4 1

WALLWASHER FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	3130 lm	0 9 0 - 7 Q 9 9 ⇕ W 0 ◪ 4 1
	3000 K	3130 lm	0 9 0 - 7 Q 9 0 ⇕ W 0 ◪ 4 1
	3500 K	3260 lm	0 9 0 - 7 Q 9 2 ⇕ W 0 ◪ 4 1
	4000 K	3330 lm	0 9 0 - 7 Q 9 1 ⇕ W 0 ◪ 4 1

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready


Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS	L·W·H (mm)	ORDER CODE
12.5/15/20/25 mm	122·122·47	0 9 0 - 7 Q 9 0 1 0 0

for UNICO Q9



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
jet black	138·138·30	0 9 0 - 7 Q 9 0 2 0 B
traffic white	138·138·30	0 9 0 - 7 Q 9 0 2 0 W

for UNICO Q9

Order options


CONTROL	⇕	COLOUR	◪	COLOUR	
non DIM	1	chrome reflector	0	jet black	RAL 9005
DALI-2	3	black reflector	B	traffic white	RAL 9016

Mounting tools accessories (optional)

DISMOUNTING TOOL

L·W·H (mm)	ORDER CODE
70·30·2	0 9 0 - 0 0 2 1 0 0

Electrical accessories (optional)



POWER SUPPLY pre-wired

Available in the configurator	see POWER SUPPLY PRE-WIRED

Aertssen Group, Beveren

Belgium

Architect
Mertens Architecten

Lighting Design
Eef Debeuf

Photographer
Kris Dekeijser



Used products



MINO 60 CIRCLE suspended



MOVE IT 25 surface / suspended system



SPOTLINE MOVE IT 25




JUST 45 MOVE IT 25 / 25 S / 45



UNICO Q9 recessed



UNICO L2 / L3 recessed



SASSO 60 round downlight recessed 1 lamp

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com



















