



# UNICO Q9

ceiling


**EN** Square surface mounted multi-downlight made of aluminium; equipped with nine individually selectable or pre-specified, customised light elements; luminaire housing can be attached to mounting plate without tools by interlock; converter integrated into luminaire housing; surface powder coated; high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering

**DE** Quadratischer Anbau-Multi-Downlight aus Aluminium; bestückt mit neun individuell wählbaren oder fix definierten, anwendungsspezifischen Optiken; Leuchtenkörper mittels Verriegelung werkzeuglos auf Montageplatte aufsetzbar; Konverter im Leuchtenkörper integriert; Oberfläche pulverbeschichtet; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; präzise Abstrahlcharakteristik mit unterschiedlichen symmetrischen Lichtverteilungen; oder mit asymmetrischer Lichtverteilung; energieeffiziente High-Power-LEDs mit sehr guter Farbwiedergabe

## Quickinfo

2700 K, 3000 K, 3500 K, 4000 K  
 CRI ≥ 90 / 2 SDCM (initial MacAdam)  
 UGR ≤ 10, UGR ≤ 16, UGR ≤ 19  
 up to 139 lm/W  
 L85 / 50000 h  
 DALI-2, non DIM  
 IP20

## Types



## Colour



## Reflector



## Light distributions



black & chrome reflector



one luminaire multiple scenes




## UNICO Q9 ceiling



## SPOT ROUND 19°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
24.6 W	2700 K	2730 lm	111 lm/W	0 9 0 - 1 Q 9 9 ⇄ K ■ ■ 2 1
	3000 K	2730 lm	111 lm/W	0 9 0 - 1 Q 9 0 ⇄ K ■ ■ 2 1
	3500 K	2840 lm	115 lm/W	0 9 0 - 1 Q 9 2 ⇄ K ■ ■ 2 1
	4000 K	2900 lm	118 lm/W	0 9 0 - 1 Q 9 1 ⇄ K ■ ■ 2 1



## MEDIUM ROUND 34°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
24.6 W	2700 K	2950 lm	120 lm/W	0 9 0 - 1 Q 9 9 ⇄ B ■ ■ 2 1
	3000 K	2950 lm	120 lm/W	0 9 0 - 1 Q 9 0 ⇄ B ■ ■ 2 1
	3500 K	3070 lm	125 lm/W	0 9 0 - 1 Q 9 2 ⇄ B ■ ■ 2 1
	4000 K	3130 lm	127 lm/W	0 9 0 - 1 Q 9 1 ⇄ B ■ ■ 2 1

## FLOOD ROUND 47°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
24.6 W	2700 K	3150 lm	128 lm/W	0 9 0 - 1 Q 9 9 ⇄ C ■ ■ 2 1
	3000 K	3150 lm	128 lm/W	0 9 0 - 1 Q 9 0 ⇄ C ■ ■ 2 1
	3500 K	3280 lm	133 lm/W	0 9 0 - 1 Q 9 2 ⇄ C ■ ■ 2 1
	4000 K	3340 lm	136 lm/W	0 9 0 - 1 Q 9 1 ⇄ C ■ ■ 2 1

## WIDE FLOOD ROUND 67°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
24.6 W	2700 K	3200 lm	130 lm/W	0 9 0 - 1 Q 9 9 ⇄ D ■ ■ 2 1
	3000 K	3200 lm	130 lm/W	0 9 0 - 1 Q 9 0 ⇄ D ■ ■ 2 1
	3500 K	3330 lm	135 lm/W	0 9 0 - 1 Q 9 2 ⇄ D ■ ■ 2 1
	4000 K	3400 lm	138 lm/W	0 9 0 - 1 Q 9 1 ⇄ D ■ ■ 2 1

## MEDIUM SQUARE 32°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
24.6 W	2700 K	2870 lm	117 lm/W	0 9 0 - 1 Q 9 9 ⇄ E ■ ■ 2 1
	3000 K	2870 lm	117 lm/W	0 9 0 - 1 Q 9 0 ⇄ E ■ ■ 2 1
	3500 K	2990 lm	122 lm/W	0 9 0 - 1 Q 9 2 ⇄ E ■ ■ 2 1
	4000 K	3050 lm	124 lm/W	0 9 0 - 1 Q 9 1 ⇄ E ■ ■ 2 1

## FLOOD SQUARE 55°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
24.6 W	2700 K	3200 lm	130 lm/W	0 9 0 - 1 Q 9 9 ⇄ F ■ ■ 2 1
	3000 K	3200 lm	130 lm/W	0 9 0 - 1 Q 9 0 ⇄ F ■ ■ 2 1
	3500 K	3330 lm	135 lm/W	0 9 0 - 1 Q 9 2 ⇄ F ■ ■ 2 1
	4000 K	3400 lm	138 lm/W	0 9 0 - 1 Q 9 1 ⇄ F ■ ■ 2 1

## Order options

CONTROL	⇄	COLOUR	■	REFLECTOR	■
non DIM	1	gold dust RAL 260-M	9	black	B
DALI-2	3	jet black RAL 9005	B	chrome	0
		white aluminium RAL 9006	G		
		traffic white RAL 9016	W		

**WIDE FLOOD SQUARE 70°, CRI ≥ 90**

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
24.6 W	2700 K	3220 lm	131 lm/W	0 9 0 - 1 Q 9 9 <input type="checkbox"/> G <input checked="" type="checkbox"/> ■ 2 1
	3000 K	3220 lm	131 lm/W	0 9 0 - 1 Q 9 0 <input type="checkbox"/> G <input checked="" type="checkbox"/> ■ 2 1
	3500 K	3350 lm	136 lm/W	0 9 0 - 1 Q 9 2 <input type="checkbox"/> G <input checked="" type="checkbox"/> ■ 2 1
	4000 K	3420 lm	139 lm/W	0 9 0 - 1 Q 9 1 <input type="checkbox"/> G <input checked="" type="checkbox"/> ■ 2 1

**WALLWASHER CRI ≥ 90**

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
24.6 W	2700 K	2480 lm	101 lm/W	0 9 0 - 1 Q 9 9 <input type="checkbox"/> A <input checked="" type="checkbox"/> 0 2 1
	3000 K	2480 lm	101 lm/W	0 9 0 - 1 Q 9 0 <input type="checkbox"/> A <input checked="" type="checkbox"/> 0 2 1
	3500 K	2590 lm	105 lm/W	0 9 0 - 1 Q 9 2 <input type="checkbox"/> A <input checked="" type="checkbox"/> 0 2 1
	4000 K	2640 lm	107 lm/W	0 9 0 - 1 Q 9 1 <input type="checkbox"/> A <input checked="" type="checkbox"/> 0 2 1

**Order options**

CONTROL		COLOUR		REFLECTOR	
non DIM	<input type="checkbox"/>	gold dust RAL 260-M	9	black	B
DALI-2	<input type="checkbox"/>	jet black RAL 9005	B	chrome	0
		white aluminium RAL 9006	G		
		traffic white RAL 9016	W		