

SPADO 150 square

recessed

EN Square luminaire housing in die-cast aluminium; with trim; suitable for ceiling thickness of 2-25mm; surface powder coated; installation without tools using snap spring closure; reflector made of polycarbonate, polished chrome; symmetric radiation characteristic; lighting level recessed; energy-efficient LEDs with very good colour rendering; external converter for ceiling insertion, for through-wiring suitable; operating device suitable for use with a central battery system

ES Cuerpo de lámpara cuadrado de fundición de aluminio; con marco; para instalación en techos de 2-25mm de grosor; superficie con recubrimiento de pintura en polvo; sencilla instalación sin herramientas mediante un enganche elástico; reflector de policarbonato, acabado en cromo pulido; característica de emisión simétrica; lámpara retrasada; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; convertidor externo para inserción en el techo, adecuado para cableado pasante; unidad de control apropiada para el funcionamiento en un sistema de batería central

Quickinfo

3000 K, 4000 K
CRI $\geq$ 80 / 3 SDCM
UGR $\leq$ 19
hasta 118 lm/W
L80 / 50000 h, L90 / 50000 h
DALI-2, non attenuable
front IP44, back IP20

Types



Color



Distribución luminosa




DiiA® standards
251, 252, 253



glare control
(UGR $\leq$ 19)



splash water
protection
(IP44)




SPADO 150 square downlight trim



WIDE FLOOD traffic white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
16.4 W	3000 K	1830 lm	112 lm/W	0 4 9 - 3 1 5 1 5 ◆ 7 0
	4000 K	1940 lm	118 lm/W	0 4 9 - 3 1 5 1 6 ◆ 7 0
27.5 W	3000 K	2990 lm	109 lm/W	0 4 9 - 3 1 5 2 5 ◆ 7 0
	4000 K	3170 lm	115 lm/W	0 4 9 - 3 1 5 2 6 ◆ 7 0

150 x 150 100



Mounting accessories (optional)

EXPOSED CONCRETE MOUNTING HOUSING

L-W-H (mm)

400-260-160

ORDER CODE

0 4 9 - 3 1 9 2 2 1 0

PRIMED CONCRETE MOUNTING HOUSING

L-W (mm)

310-170

ORDER CODE

0 4 9 - 3 1 9 1 4 1 0

Order options

CONTROL

non DIM

DALI-2



COLOUR

traffic white

RAL 9016

1

3