



SASSO 100 round

suspended


EN Cylindrical spotlight made of aluminium; surface light inset lacquered; surface housing powder coated; pendant fitting with cable suspension; incl. feed (black or white); can be individually shortened; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; canopy for thorough wiring; converter included in canopy

ES Proyector cilíndrico de aluminio; superf. de inserto lumin. pintada; superf. carcasa con recubr. de polvo; suspendido con cable; incl. cable de alimentación (negro o blanco); se puede acortar; proyección precisa con óptica de lente de alta calidad; Chip on Board que proporciona una máxima eficiencia; no sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática; baldaquino para cableado pasante; convertidor integrado en el baldaquino

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI $\geq$ 90 / 2 SDCM
UGR $\leq$ 13, UGR $\leq$ 16, UGR $\leq$ 19
hasta 99 lm/W
L80 / 50000 h
DALI-2, non atenuable
IP20

Types



Color



Color interno



Distribución luminosa



glare control
(UGR $\leq$ 16)



easy mounting
no visible
screws



CRI $\geq$ 95 2
SDCM
(optional)



SASSO 100 round downlight suspended



SPOT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
17.9 W	2700 K	1430 lm	80 lm/W	0 4 8 - 3 4 2 0 9 S
	3000 K	1480 lm	83 lm/W	0 4 8 - 3 4 2 0 0 S
	3500 K	1510 lm	84 lm/W	0 4 8 - 3 4 2 0 2 S
	4000 K	1550 lm	87 lm/W	0 4 8 - 3 4 2 0 1 S

The data values for the luminous flux may differ for specific order options by -6%.

MEDIUM CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
17.9 W	2700 K	1440 lm	80 lm/W	0 4 8 - 3 4 2 0 9 M
	3000 K	1480 lm	83 lm/W	0 4 8 - 3 4 2 0 0 M
	3500 K	1520 lm	85 lm/W	0 4 8 - 3 4 2 0 2 M
	4000 K	1550 lm	87 lm/W	0 4 8 - 3 4 2 0 1 M

The data values for the luminous flux may differ for specific order options by -7%.

FLOOD CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
17.9 W	2700 K	1600 lm	89 lm/W	0 4 8 - 3 4 2 0 9 F
	3000 K	1650 lm	92 lm/W	0 4 8 - 3 4 2 0 0 F
	3500 K	1690 lm	94 lm/W	0 4 8 - 3 4 2 0 2 F
	4000 K	1720 lm	96 lm/W	0 4 8 - 3 4 2 0 1 F

WIDE FLOOD CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
17.9 W	2700 K	1640 lm	92 lm/W	0 4 8 - 3 4 2 0 9 W
	3000 K	1700 lm	95 lm/W	0 4 8 - 3 4 2 0 0 W
	3500 K	1730 lm	97 lm/W	0 4 8 - 3 4 2 0 2 W
	4000 K	1770 lm	99 lm/W	0 4 8 - 3 4 2 0 1 W

Optical accessories (optional)

HONEYCOMB LOUVER

TYPE	COLOUR	Ø-H (mm)	ORDER CODE
for BO 55 SASSO 100	jet black	50-3	0 0 7 - 1 9 6 5 5 9 8

Order options

CONTROL		COLOUR		INNER COLOUR	
non DIM	1	jet black RAL 9005	1	jet black	1
DALI-2	3	traffic white RAL 9016	7	matt silver	4
				traffic white	7
				gold dust	9

Waterdrop Headquarters, Vienna

Austria

Arquitecto


AllesWirdGut Architekten

Fotografía

tschinkersten fotografie



Productos utilizados



JANE semi-recessed / surface / suspended



BETO suspended



SASSO 100 round ceiling



SASSO 100 round suspended

