





Quickinfo

4000 K
 CRI ≥ 90 / 3 SDCM
 UGR ≤ 19
 hasta 15,500 lm / $\uparrow$ 8,050 lm
 hasta 120 lm/W
 L90 / 50000 h
 DALI-2
 Microprismatic
 IP20

Types



Color



Distribución luminosa



TASK angular

suspended

EN Rectangular suspended luminaire, consisting of single L-shaped or rectangular elements; Luminaire housing made of aluminium with rounded edges; ultra low-profile design (only 15 mm); surface powder coated; cable suspension, toolless height adjustment; convenient quick mounting system without tools; incl. feeder cable; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; canopy for through wiring; optional acoustic elements available


ES Luminaria pendular rectangular, compuesta por elementos individuales en forma de L o bien rectangulares; Cuerpo de luminaria de aluminio con cantos redondeados; perfil extra plano (sólo 15 mm); superficie con recubrimiento de pintura en polvo; suspensión cable altura regulable sin herram.; sistema de montaje rápido sin herramientas; incl. cable de alimentación; distribución de luz directa a través de cuerpo LGP (Light Guiding Prism); la luz acoplada lateralmente se orienta hacia abajo por medio de un grabado por láser; proporción indirecta con pletinas propias para un flujo luminoso aumentado y una iluminación máxima del techo; iluminación homogénea; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; baldaquino para cableado pasante; opcional elementos acústicos disponible




DiiA® standards
 251, 252, 253




clicksystem




microprismatic
 UGR ≤ 19



CRI ≥ 98
XPECTRUM
 (optional)





TASK angular suspended




DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
197.0 W	4000 K	↓15500/↑18050 lm	120 lm/W	0 5 9 - 5 2 8 3 1 3 ☒ K




TASK long angular suspended




DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

COLOUR TEMP.	ORDER CODE
4000 K	0 5 9 - 5 2 8 4 1 3 ☒ K



Planning Information



TASK long angular, 280W, 4000K,
direct/indirect power

ROOM VALUES	
Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8
Suspension height	2.25 m

CALCULATION SURFACE	
Surface dimensions	3.2 × 1.2 m
Surface height	0.75 m
Average illuminance (E _m)	> 500 lx
Uniformity (U ₀)	> 0.6

GLARE EVALUATION	
Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19

Order options

COLOUR	☒
pure white RAL 9010	7
jet black RAL 9005	8

Community Windpower, Frodsham


Reino Unido

Fotografía

Paul Karalius




Productos utilizados



**TASK angular
suspended**



**TASK round
suspended**



**TASK circle
suspended**

