



625 1210 1500 2375



TUBO 60

surface


EN Supporting profile in extruded aluminium; end cap in aluminium; surface powder coated; suitable for wall or ceiling mounting; light control via high-quality lens system for maximum, homogeneous illumination; completely homogeneously illuminated, cylindrical HPO (High Performance Opal) cover; energy-efficient LEDs with very good colour rendering

ES Perfil soporte fabricado en aluminio; tapas finales de aluminio; superficie con recubrimiento de pintura en polvo; apropiada para montaje en techo y paredes; direccionam. de luz con óptica de lente alta calidad para alumbr. techo máx. y homog.; difusor HPO (High Performance Opal) de alumbrado totalmente homogéneo; LEDS de alta eficiencia que proporcionan una alta reproducción cromática

Quickinfo

3000 K, 4000 K
CRI $\geq$ 80, CRI $\geq$ 90 / 3 SDCM
hasta 3,060 lm/m
hasta 133 lm/W
L90 / 50000 h
DALI-2
High Performance Opal
IP20

Types



Color




Distribución luminosa




driver
integrated



system solution



uniform
illumination



TUBO 60 surface



OPAL DALI-2



SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	SYSTEM	ORDER CODE
13.9 W	625 mm	3000 K	80	1590 lm	114 lm/W	0 5 8 - 3 1 1 2 5 3 ☒ O
			90	1370 lm	99 lm/W	0 5 8 - 3 1 1 2 0 3 ☒ O
		4000 K	80	1810 lm	130 lm/W	0 5 8 - 3 1 1 2 6 3 ☒ O
			90	1480 lm	106 lm/W	0 5 8 - 3 1 1 2 1 3 ☒ O
27.9 W	1210 mm	3000 K	80	3180 lm	114 lm/W	0 5 8 - 3 1 1 4 5 3 ☒ O
			90	2740 lm	98 lm/W	0 5 8 - 3 1 1 4 0 3 ☒ O
		4000 K	80	3620 lm	130 lm/W	0 5 8 - 3 1 1 4 6 3 ☒ O
			90	2960 lm	106 lm/W	0 5 8 - 3 1 1 4 1 3 ☒ O
34.0 W	1500 mm	3000 K	80	3950 lm	116 lm/W	0 5 8 - 3 1 1 5 5 3 ☒ O
			90	3400 lm	100 lm/W	0 5 8 - 3 1 1 5 0 3 ☒ O
		4000 K	80	4490 lm	132 lm/W	0 5 8 - 3 1 1 5 6 3 ☒ O
			90	3670 lm	108 lm/W	0 5 8 - 3 1 1 5 1 3 ☒ O
54.0 W	2375 mm	3000 K	80	6300 lm	117 lm/W	0 5 8 - 3 1 1 8 5 3 ☒ O
			90	5430 lm	101 lm/W	0 5 8 - 3 1 1 8 0 3 ☒ O
		4000 K	80	7170 lm	133 lm/W	0 5 8 - 3 1 1 8 6 3 ☒ O
			90	5870 lm	109 lm/W	0 5 8 - 3 1 1 8 1 3 ☒ O

Order options

COLOUR	
pure white RAL 9010	☒ 7
jet black RAL 9005	☒ 8