



TASK square

free standing


EN Free standing luminaire with square luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15 mm); steel round downpipe; pedestal with recess for table base; surface powder coated; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3m) with safety plug

ES Luminaria de pie con cabezal de luminaria cuadrado de aluminio y cantos redondeados; perfil extra plano (sólo 15 mm); Tubo de acero; pedestal para integrarse como base de mesa; superficie con recubrimiento de pintura en polvo; distribución de luz directa a través de cuerpo LGP (Light Guiding Prism); la luz acoplada lateralmente se orienta hacia abajo por medio de un grabado por láser; proporción indirecta con pletinas propias para un flujo luminoso aumentado y una iluminación máxima del techo; iluminación homogénea; LEDs de alta eficiencia que proporcionan una alta reproducción cromática; interruptor montado en el tubo; incluye 3 metros de cable de conexión

Quickinfo

3000 K, 4000 K
CRI $\geq$ 90 / 3 SDCM
UGR $\leq$ 10
hasta : 2,420 lm / $\uparrow$ 10,700 lm
hasta 143 lm/W
L90 / 50000 h
sensor ESSENTIAL independiente,
touch DIM en el poste
Microprismatic
IP20

Types



Color




Distribución luminosa




suitable for
fourfold
workstation



lighting control
by touch DIM
on pole



CRI $\geq$ 98
XPECTRUM
(optional)




TASK square free standing



DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
92.0 W	3000 K	↓2280/↑10000 lm	133 lm/W	0 5 9 - 2 9 3 2 0 Z
	4000 K	↓2420/↑10700 lm	143 lm/W	0 5 9 - 2 9 3 2 1 Z

Planning Information



TASK square free standing

92 W, 4000 K, direct/indirect power

ROOM VALUES

Room dimensions	7.2 × 4 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8

CALCULATION SURFACE

Surface dimensions	4.8 × 0.6 m
Surface height	0.75 m
Average illuminance (E_m)	> 500 lx

GLARE EVALUATION

Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19
65° ≤ 3000 cd/m²	

Order options

CONTROL

touch DIM on pole	5
stand alone ESSENTIAL sensor	7



COLOUR

white aluminium RAL 9006	6
pure white RAL 9010	7
jet black RAL 9005	8
special colours	X

Office MyHammer

Alemania

Arquitecto

designfunktion
Gesellschaft für
moderne Einrichtung
Berlin mbH

Fotografía

Werner Huthmacher



Productos utilizados



**TASK square free
standing**

