



TASK

wall


EN Rectangular housing made of aluminium with rounded edges; ultra low-profile design (only 15 mm); surface powder coated; suitable for wall mounting; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; indirect component with special PCBs with asymmetrical light distribution; for optimum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering

ES Cuerpo de luminaria rectangular de aluminio con cantos redondeados; perfil extra plano (sólo 15 mm); superficie con recubrimiento de pintura en polvo; apropiada para montaje pared; distribución de luz directa a través de cuerpo LGP (Light Guiding Prism); la luz acoplada lateralmente se orienta hacia abajo por medio de un grabado por láser; orientación luz por medio de un elemento altamente reflectante; proporción indirecta con pletinas propias con distribución de luz asimétrica; para una iluminación óptima del techo; iluminación homogénea; LEDS de alta eficiencia que proporcionan una alta reproducción cromática

Quickinfo

3000 K, 4000 K
CRI $\geq$ 90 / 3 SDCM
hasta ↓ 1,970 lm / ↑ 3,760 lm
hasta 125 lm/W
L90 / 50000 h
DALI-2
Microprismatic
IP20

Types




Color




Distribución luminosa



asymmetrical
ceiling
illumination




TASK wall



MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
46.0 W	3000 K	↓1850/↑3530 lm	117 lm/W	0 5 9 - 2 0 3 2 0 3 Z
	4000 K	↓1970/↑3760 lm	125 lm/W	0 5 9 - 2 0 3 2 1 3 Z

Planning Information



TASK wall
46 W, 4000 K, direct / indirect power

ROOM VALUES	
Room dimensions	5.4 × 4.0 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8
Mounting height	2.25 m

CALCULATION SURFACE	
Surface dimensions	Floor
Surface height	0 m

GLARE EVALUATION	
Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19

Order options

COLOUR	
pure white RAL 9010	7
jet black RAL 9005	8