



PABLO multilens


EN Track light made of die-cast aluminium; surface powder coated; 360° rotatable and 310° tiltable; converter installed in aluminium spotlight housing; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; exchangeable additional lenses; precise radiation characteristics with different beam angles; installed and exchanged without tools; optical attachments as accessories; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter fixation optionally without tools by means of knurled screw or set screw (screwdriver required); point outlet, either in surface mounted housing or recessed housing, as an accessory

ES Proyector de carril electrificado de fundición de aluminio inyectado; superficie con recubrimiento de pintura en polvo; giratorio 360° y orientable 310°; convertidor montado en carcasa de proyector de aluminio; con tecnología COB (Chip on Board) para proporcionar una máxima eficiencia; no sombras múltiples; LEDs de alta eficiencia que proporcionan una alta reproducción cromática; lentes reemplazables; característica de emisión precisa con diferentes ángulos de emisión; intercambiable sin herramienta; los accesorios ópticos como accesorios; adaptador para instalación sin herramientas; los accesorios ópticos como accesorios; adaptador para instalación sin herramienta con tornillo moleteado o tornillo de sujeción (destornillador necesario); base para techo, opcionalmente en carcasa superpuesta o carcasa empotrada, como accesorio

Quickinfo

3000 K, 4000 K
CRI $\geq$ 90 / 2 SDCM
hasta 73 lm/W
L85 / 50000 h
DIM POTI
IP20

Types



Color



Distribución luminosa



compatible with
MOVE IT PRO



DiiA® standards
251, 252, 253



interchangeable
diffusion
sheets



360° rotatable,
310° tiltable



DIM POTI /
rotation lock




PABLO multilens track




WIDE FLOOD / FLOOD / MEDIUM / SPOT / SUPER SPOT / OVAL DIM POT, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
14.7 W	3000 K	1010 lm	69 lm/W	1 8 0 - 5 7 0 5 8
	4000 K	1090 lm	74 lm/W	1 8 0 - 5 7 0 6 8


incl. 5 pcs. interchangeable diffusion sheets



Planning Information



Mounting accessories (optional)



RECESSED HOUSING / POINT OUTLET ceiling thickness, 1-30 mm

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	151-60	1 8 6 - 0 7 2 2 7 7
jet black	151-60	1 8 6 - 0 7 2 2 7 8



SURFACE HOUSING / POINT OUTLET

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	120-32	1 8 6 - 0 7 2 2 8 7
jet black	120-32	1 8 6 - 0 7 2 2 8 8

Optical accessories (optional)



DIFFUSION SHEET FOR SUPERSPOT

TYPE	ORDER CODE
for a better homogeneous illumination	0 8 0 - 5 9 0 0 0 3 0



OVAL FILTER

TYPE	ORDER CODE
60 x 15°	0 8 0 - 5 9 0 0 0 2 0

Order options

MOUNTING	Ø	COLOUR	✓
set screw (tool required)	1	traffic white RAL 9016	7
tool-free fixation	2	jet black RAL 9005	8