



SONO LOOP IP54

surface


EN Round luminaire housing in die-cast aluminium; surface powder coated; fitted bezel in rolled, seamless welded aluminium profile; suitable for wall or ceiling mounting; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

ES Cuerpo redondo de aluminio; superficie con recubrimiento de pintura en polvo; anillo superpuesto de perfil de aluminio enrollado y soldado sin costuras; apropiada para montaje en techo y paredes; tapa PMMA iluminada homogéneamente con acabado satinado; luminancia idéntica en todos los tamaños; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; luminaria con abertura de 2 orificios para integrar cableado y sencilla conexión

Quickinfo

3000 K, 4000 K
CRI \geq 80 / 3 SDCM
hasta 133 lm/W
L90 / 50000 h
DALI-2, non atenuable
Opal
IP54, IK07

Types



Color



Distribución luminosa



DiiA® standards
251, 252, 253




easy mounting
by click-
mechanism



dust & insect
protection (IP
54)



tunable white
2700 – 6500 K
(optional)





SONO LOOP 260 IP54 surface



OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.6 W	3000 K	881 lm	116 lm/W	8 7 1 - 8 1 2 6 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	933 lm	123 lm/W	8 7 1 - 8 1 2 6 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O




SONO LOOP 350 IP54 surface



OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
15.9 W	3000 K	1940 lm	122 lm/W	8 7 1 - 8 1 3 6 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	2050 lm	129 lm/W	8 7 1 - 8 1 3 6 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O




SONO LOOP 450 IP54 surface




OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
23.2 W	3000 K	2840 lm	122 lm/W	8 7 1 - 8 1 4 6 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	3010 lm	130 lm/W	8 7 1 - 8 1 4 6 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O



Order options

CONTROL		COLOUR	
non DIM	1	pure white RAL 9010	7
DALI-2	3	grey aluminium RAL 9007	D



SONO LOOP 600 IP54 surface



OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
43.0 W	3000 K	5410 lm	126 lm/W	8 7 1 - 8 1 5 6 5 O
	4000 K	5730 lm	133 lm/W	8 7 1 - 8 1 5 6 6 O

Order options

CONTROL		COLOUR	
non DIM	1	pure white RAL 9010	7
DALI-2	3	grey aluminium RAL 9007	D