



## SONO LOOP IP54

surface


**EN** Round luminaire housing in die-cast aluminium; surface powder coated; fitted bezel in rolled, seamless welded aluminium profile; suitable for wall or ceiling mounting; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

**ES** Cuerpo redondo de aluminio; superficie con recubrimiento de pintura en polvo; anillo superpuesto de perfil de aluminio enrollado y soldado sin costuras; apropiada para montaje en techo y paredes; tapa PMMA iluminada homogéneamente con acabado sanitado; luminancia idéntica en todos los tamaños; LEDs de alta eficiencia que proporcionan una alta reproducción cromática; luminaria con abertura de 2 orificios para integrar cableado y sencilla conexión

### Quickinfo

3000 K, 4000 K  
CRI  $\geq$  80, 3 SDCM  
uo to 133lm/W  
L90 @ 50000h  
non DIM, DALI-2  
opal cover  
IK 07, IP54

### Types



### Colours



### Light distribution



direct




DiiA® standards  
251, 252, 253



easy mounting by  
click-mechanism



dust and insect  
protection (IP54)



tunable white  
2700–6500K

## Order options

### IP RATING

IP54

### COLOUR TEMPERATURE

3000K 5  
4000K 6

### CONTROL

non DIM 1  
DALI-2 3

### MATERIAL COLOUR

○ pure white RAL 9010 7  
● grey aluminium RAL 9007 D

### LIGHT OPTIC COVER

opal

## Options on request

### COLOUR RENDERING INDEX

CRI ≥ 90

### COLOUR TEMPERATURE


tunable white 2700–6500K

DALI-2 DT8

### CONTROL

RCS Master (☺)

RCS Slave (☺)




## SONO LOOP 260 surface



### IP54 LUMINAIRE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
7.6W	3000K	881lm	8 7 1 - 8 1 2 6
	4000K	933lm	




## SONO LOOP 350 surface



### IP54 LUMINAIRE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
15.9W	3000K	1940lm	8 7 1 - 8 1 3 6
	4000K	2060lm	




## SONO LOOP 450 surface



### IP54 LUMINAIRE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
23.2W	3000K	2850lm	8 7 1 - 8 1 4 6
	4000K	3010lm	



## SONO LOOP 600 surface



### IP54 LUMINAIRE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
43W	3000K	5410lm	8 7 1 - 8 1 5 6
	4000K	5730lm	