



SQUADRO wallwasher

track


EN Track light in die cast aluminium in two different types (4 lamps or 2x4 lamps) and with 2 types of light modules (for shelf floor washer and wall floor washer); surface powder coated; aisle spotlight with special, multi-free-form, facet effect surface reflectors for high precision light control; precise shelf and aisle zone lighting, optimum longitudinal glare control for high viewing comfort in the aisle zone, adjustable light modules; COB (Chip on Board) technology for maximum efficiency; efficient LEDs with very good colour rendering; IP 40 protection glass available as an accessory; including attachment for linear alignment of the spotlights

ES Foco de aluminio de carril electrificado en 2 diferentes variantes (4 o 2x4 lámparas) y con 2 módulos de iluminación diferentes (para shelf floor washer y wall floor washer); superficie con recubrimiento de pintura en polvo; foco de pasillos con reflect. especiales multisuperficie de forma libre con óptica facetada para una orient. de la luz sumamente precisa; ilumin. precisa de estanterías y pasillos, evitando de forma óptima el deslumbram. longitudinal para un elevado confort visual en el pasillo, módulos de iluminación ajustables; Chip on Board para máx. eficiencia; LEDs eficientes con una muy buena reprod. cromática; vidrio protector IP 40 como accesorio; incluye accesorio para la correcta alineación de la luminaria

Quickinfo

3000K, 4000K
CRI ≥ 80, 3 SDCM
up to 134lm/W
L80 @ 50000h
non DIM, DALI-2

Types



Colours




Light distributions



DiiA® standards
251, 252, 253



glare-free reflector
longitudinally &
transversely



+20° up to -15°
tiltable

Order options


COLOUR TEMPERATURE	☐☐
3000K	5
4000K	6

CONTROL	⬆️⬆️
non DIM	1
DALI-2	3


MATERIAL COLOUR	☑️
☐ traffic white RAL 9016	7
● jet black RAL 9005	8

REFLECTOR	▲
shelf floor washer	S
wall floor washer	A
1×shelf/1×wall floor washer*	B

*only for 2×4 lamps




Light distributions




1×4 lamps
shelf floor washer

1×4 lamps
wall floor washer



2×4 lamps
shelf floor washer

2×4 lamps
wall floor washer



2×4 lamps
1×shelf/1×wall floor washer


LUMINOUS FLUX value calculated for 4000K (3000K -5%), colour white, wall floor washer

SQUADRO wallwasher track




1×4 LAMPS SINGLE-SIDED

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
51W	6610lm	1 4 9 - 2 2 3 1 ☐☐☐▲



2×4 LAMPS DOUBLE-SIDED

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
86W	2×5760lm	1 4 9 - 2 2 4 0 ☐☐☐▲
101W	2×6490lm	1 4 9 - 2 2 4 1 ☐☐☐▲




Optical accessories

IP 40 PROTECTION GLASS


TYPE	ORDER CODE
1×4 lamps/single-sided	0 4 9 - 2 9 3 0 0 1 0
2×4 lamps/double-sided	0 4 9 - 2 9 4 0 0 1 0

Technical data

SQUADRO shelf floor washer, 1×4 lamps, +5° tilt, 51W, 3000K



SQUADRO wall floor washer, 1×4 lamps, +5° tilt, 51W, 3000K



ROOM VALUES	CALCULATION SURFACE
Wall dimensions H = 3.5m W = 10.8m	Surface dimensions 10.8×3.5m
Distance to wall B = 1.3m	Surface height 0 – 3.5m
Aisle width 2.6m	
Reflection factor 0.7 0.7 0.2	Eye level 👁️ 1.35m – 1.75m
Maintenance factor 0.9	



Types



Colours



TRACK 3-phase
recessed/surface/suspended



curve connector



optimised adapter integration

TRACK recessed

Order options

CONTROL

non DIM

DALI-2

MATERIAL COLOUR

- pure white RAL 9010 7
- jet black RAL 9005 8

Pole options



TRACK 3-phase/3-phase + DALI-2-bus



TRACK 240V-16A

L (mm)	ORDER CODE
2000	186-012213
3000	186-012313
4000	186-012413

end cap 186-022011

end feed left 186-022313
 end feed right 186-022413
 middle feed 186-021323

CONNECTORS 240V-16A

TYPE **ORDER CODE**
 linear connector 186-021113

I-connector 186-022123

L-connector right 186-022133
 L-connector left 186-022233


T-connector right (poles internal) 186-022143
 T-connector left (poles internal) 186-022243
 T-connector right (poles external) 186-022173
 T-connector left (poles external) 186-022273

X-connector 186-022153

MOUNTING ACCESSORIES

TYPE **ORDER CODE**
 clip 186-0225110

cutting tool 186-0219110



TRACK

surface/suspended

Order options

CONTROL

non DIM
 DALI-2

MATERIAL COLOUR

- pure white RAL 9010 7
- white aluminium RAL 9006 6
- jet black RAL 9005 8

Pole options



TRACK 3-phase/3-phase + DALI-2-bus



TRACK 240V-16A

L (mm)	ORDER CODE
1000	186-011123
2000	186-011223
3000	186-011323
4000	186-011423

end cap 186-021011

end feed left 186-021313
 end feed right 186-021413
 middle feed* 186-021323

*only available in white and black

CONNECTORS 240V-16A

TYPE ORDER CODE
 linear connector 186-021113

I-connector 186-021123

L-connector right 186-021133

L-connector left 186-021233

T-connector right (poles internal) 186-021143

T-connector left (poles internal) 186-021243

T-connector right (poles external) 186-021173

T-connector left (poles external) 186-021273

X-connector 186-021153

adjustable corner connector 186-021163

MOUNTING ACCESSORIES

TYPE ORDER CODE
 ceiling clip 186-021511

pendant clip cable 186-021521

pendant clip rod 186-021541

joiner piece cable 186-021531

joiner piece rod 186-021551

cutting tool 186-0219110


SUSPENSION KIT

TYPE ORDER CODE
 pendant 1000 186-021611

cable 1500 186-0217110

cable 3000 186-0217210

cable 6200 186-0217310



TRACK high

surface/suspended

Order options

CONTROL

non DIM

DALI-2

MATERIAL COLOUR

○ pure white RAL 9010 7


● jet black RAL 9005 8

Options on request


LIGHT OPTIC COVER

inset indirect


Pole options




poles internal left



poles internal right



poles external left



poles external right



poles end feed left



poles end feed right

TRACK high 3-phase/3-phase + DALI-2-bus



TRACK 240V-16A

L (mm)	ORDER CODE
1000	186-016113
2000	186-016213
3000	186-016313
4000	186-016413

end cap 186-026011

end feed left 186-026313

end feed right 186-026413

middle feed 186-021323

CONNECTORS 240V-16A

TYPE
linear connector 186-026113

L-connector 186-026123

L-connector right 186-026133

L-connector left 186-026233

T-connector right (poles internal) 186-026143

T-connector left (poles internal) 186-026243

T-connector right (poles external) 186-026173

T-connector left (poles external) 186-026273

X-connector 186-026153

MOUNTING ACCESSORIES

TYPE
pendant clip cable 186-0265210
pendant sheet metal clip 186-0215220
pendant clip rod 186-0265410

joiner piece cable 186-0265310

joiner piece rod 186-0265510

cutting tool 186-0219110


SUSPENSION KIT

TYPE
pendant 1000 186-0216110

cable 1500 186-0217110

cable 3000 186-0217210

cable 6200 186-0217310



TRACK round surface/suspended

Order options

CONTROL

non DIM _____
DALI-2 _____

MATERIAL COLOUR

○ pure white RAL 9010 7
● jet black RAL 9005 8

Options on request

CONNECTOR

T-connector _____
X-connector _____

TRACK round 3-phase/3-phase + DALI-2-bus




TRACK 240V-16A

L (mm)	ORDER CODE
1000	186-015113 <input checked="" type="checkbox"/>
2000	186-015213 <input checked="" type="checkbox"/>
3000	186-015313 <input checked="" type="checkbox"/>
4000	186-015413 <input checked="" type="checkbox"/>



TRACK CURVE 240V-16A

TYPE	ORDER CODE
R 500 90° left	186-015853 <input checked="" type="checkbox"/>
R 500 90° right	186-015863 <input checked="" type="checkbox"/>



end cap _____ 186-025011




end feed left _____ 186-025313
end feed right _____ 186-025413
middle feed _____ 186-021323




CONNECTORS 240V-16A

linear connector _____ 186-021113



L-connector right _____ 186-025133
L-connector left _____ 186-025233



MOUNTING ACCESSORIES

pendant clip cable _____ 186-025521
pendant clip rod _____ 186-025541

joiner piece cable _____ 186-025531
joiner piece rod _____ 186-025551

cutting tool _____ 186-0219110

SUSPENSION KIT

pendant 1000 _____ 186-021611

cable 1500 _____ 186-0217110
cable 3000 _____ 186-0217210
cable 6200 _____ 186-0217310