

MITA circle 240/450

recessed with trim


EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim; optional: blind cover to cover the cut-out available as an accessory; suitable for ceiling thickness of 2-25 mm; surface powder coated; high-gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering

ES Cuerpo con forma de anillo y fabricado en aluminio; forma extremadamente esbelta; luminaria empotrable con marco; opcional: cubierta opaca para inserción en recorte de techo disponible como accesorio adicional; para instalación en techos de 2-25mm de grosor; superficie con recubrimiento de pintura en polvo; reflector de alto brillo con óptica facetada; LEDS de alta eficiencia que proporcionan una alta reproducción cromática

Quickinfo

3000 K, 4000 K, TW
 CRI ≥ 80, 3 SDCM
 UGR ≤ 19 / 65° ≤ 1500 cd/m²
 up to 155 lm/W
 L95 @ 50 000 h
 DALI-2
 reflector (UGR ≤ 19)

Types



Colours




Light distribution



suitable for plaster-board or grid ceilings



DIN EN 12464-1
 UGR ≤ 19



tunable white
 2700-6500K

Order options

COLOUR TEMPERATURE

3000K	5
4000K	6
tunable white 2700–6500K*	D

*DALI-2 DT8

CONTROL

DALI-2

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

LIGHT OPTIC COLOUR

chrome reflector	R
black reflector	B

LIGHT OPTIC COVER

reflector (UGR ≤ 19)

Options on request

COLOUR RENDERING INDEX



CRI ≥ 90

GRID CEILING MOUNTING

installed in module 600 × 600 mm
installed in module 625 × 625 mm

INLAY

sensor
emergency light



MITA circle 240 trim



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
13.9W	3000K	1950lm	074-8114 3 3
	4000K	2160lm	

MITA circle 450 trim



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30W	3000K	4220lm	074-8116 3 3
	4000K	4650lm	
41W*	3000K	5490lm	074-8126 3 3
	4000K	6060lm	


*not for tunable white

Accessories

BLIND COVER

TYPE	ORDER CODE
MITA 240 circle recessed	074-891141 3
MITA 450 circle recessed	074-891161 3

Light distribution



reflector (UGR ≤ 19)
direct

LUMINOUS FLUX value calculated for
CRI ≥ 80, colour white, reflector chrome