

SONO flex

recessed with trim


EN Round recessed luminaire in aluminium, consisting of (SONO) light housing and recessed housing; housing with trim suitable for installation in plasterboard ceilings; suitable for ceiling thickness of 10-25 mm; optionally: installation in concrete ceilings with a special installation housing (available as an accessory); surface powder coated; luminaire installs in housing without tools optionally flush or protruding by 25 mm; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

ES Lámpara empotrable de aluminio, con cuerpo de lámpara (SONO) y carcasa de montaje; accesorio para montaje con marco en techos de yeso; para instalación en techos de 10-25 mm de grosor; opcional: empotramiento en techos de hormigón mediante caja de empotramiento en hormigón (disponible como accesorio); superficie con recubrimiento de pintura en polvo; luminaria empotrada para montaje sin herramientas o en superficies salientes de 25 mm; tapa PMMA iluminada homogéneamente con acabado satinado; luminancia idéntica en todos los tamaños; LEDs de alta eficiencia que proporcionan una alta reproducción cromática; luminaria con abertura de 2 orificios para integrar cableado y sencilla conexión

Quickinfo

3000 K, 4000 K
CRI ≥ 80, 3 SDCM
up to 133 lm/W
L90 @ 50 000 h
non DIM, DALI-2
opal cover
IP 50

Types



Colour



Light distribution



direct




DiiA® standards
251, 252, 253



flexible jut out
0 or 25 mm



dust and insect
protection (IP50)



tunable white
2700-6500K

Order options

IP RATING

IP50

COLOUR TEMPERATURE

3000K 5
4000K 6

CONTROL

non DIM 1
DALI-2 3

MATERIAL COLOUR

○ pure white RAL 9010

LIGHT OPTIC COVER

opal

Options on request

COLOUR RENDERING INDEX

CRI ≥ 90

COLOUR TEMPERATURE

tunable white 2700–6500K

DALI-2 DT8


CONTROL

RCS Master (☉)

RCS Slave (☉)

EMERGENCY LIGHT

3h accupack




SONO FLEX 350 trim



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
15.9W	3000K	1940lm	063-3238::70
	4000K	2060lm	




SONO FLEX 450 trim



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
23.2W	3000K	2850lm	063-3248::70
	4000K	3010lm	



SONO FLEX 600 trim



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
43W	3000K	5410lm	063-3258::70
	4000K	5730lm	

Accessories

CONCRETE INSTALLATION HOUSING

TYPE	Ø-H (mm)	ORDER CODE
SONO FLEX 350	364-107	063-2238100
SONO FLEX 450	464-107	063-2248100
SONO FLEX 600	614-107	063-2258100