

LINEA opal / 1 spot

wall

058-6178D47CH



Proyecto / Tipo

Notas

Cantidad / Fecha



General

Pared , Superficie

blanco , RAL9010 ¹

3350 lm/m

IP20

indirecto 4030 lm

directa 4030 lm

total 8060 lm

inclinable máx 89°

141 lm

LED

3000 K²-tunable white³

2700 K - 5000 K

CRI ≥ 90

L80 / 50000 h²-L85 / 50000 h³

seguridad fotobio. RG 0 - sin riesgo

MacAdam inicial ≤ 3 SDCM

R_g: 99 , R_f: 90 , R₍₁₋₁₅₎: 88

MR 0.53

MDER 0.48

Óptico

High Performance Opal

PstLM ≤ 1.0 ⁴

SVM ≤ 0.4 ⁴

Flood

ángulo de haz 23°

Eléctrico

DALI-2 / interruptor (sólo focos)

2.2²-83³ W

CP1 220-240V

64²-97³ lm/W

1 DALI Addr.

35 W/m

Físico

longitud 2510 mm


ancho 40 mm

altura 100 mm

derecha

¹ Código RAL ² Foco ³ Lineal
⁴ Valor del producto continente a plena carga (no atenuado)


Distribución luminosa



flood 23° Spot

h (m)	E0° (lx)	ø (m)
1	584	0.41
2	146	0.83
3	65	1.24
4	37	1.65
5	23	2.07

Diseño del producto



Instrucciones de montaje

