

LINEA opal / 2 spots

wall

058-6178638DH



Proyecto / Tipo _____

Notas _____

Cantidad / Fecha _____



General

Pared , Superficie _____

inclinable máx 89° _____

negro , RAL9005 ¹ _____

IP20 _____

344 lm _____

LED

3000 K²-4000 K³ _____

CRI ≥ 97²-90³ _____

L95 / 50000 h²-L85 / 50000 h³ _____

seguridad fotobio. RG 0 - sin riesgo _____

MacAdam inicial ≤ 3 SDCM _____

R_g: 92²-98³ , R_f: 86²-90³ , R_(f-l): 94²-88³ _____

MR 0.53²-0.76³ _____

MDER 0.48²-0.69³ _____

Óptico

Flood _____

ángulo de haz 30° _____

PstLM ≤ 1.0 ⁴ _____

SVM ≤ 0.4 ⁴ _____

High Performance Opal _____

Eléctrico

DALI-2 _____

5.4²-70³ W _____

CP1 220-240V _____

64²-110³ lm/W _____

2²-1³ DALI Addr. _____


Físico

longitud 2610 mm _____

ancho 40 mm _____

altura 100 mm _____


Distribución luminosa



flood 30° Spot

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 419 | 0.54 |
| 2 | 105 | 1.09 |
| 3 | 47 | 1.63 |
| 4 | 26 | 2.17 |
| 5 | 17 | 2.72 |

Diseño del producto



¹ Código RAL ² Foco ³ Lineal
⁴ Valor del producto continente a plena carga (no atenuado)

Instrucciones de montaje

