

LINEA opal / 1 spot

wall

058-6178637BH



Proyecto / Tipo

Notas

Cantidad / Fecha



General

Pared , Superficie

blanco , RAL9010 ¹

3200 lm/m

IP20

indirecto 3850 lm

directa 3850 lm

total 7700 lm

inclinable máx 89°

172 lm

LED

3000 K²-4000 K³

CRI ≥ 97²-90³

L95 / 50000 h²-L85 / 50000 h³

seguridad fotobio. RG 0 - sin riesgo

MacAdam inicial ≤ 3 SDCM

R_g: 92²-98³ , R_f: 86²-90³ , R_{f(1-15)}: 94²-88³

MR 0.53²-0.76³

MDER 0.48²-0.69³

Óptico

High Performance Opal

PstLM ≤ 1.0 ⁴

SVM ≤ 0.4 ⁴

Flood

ángulo de haz 30°

Eléctrico

DALI-2

2.7²-70³ W

CP1 220-240V

64²-110³ lm/W

1 DALI Addr.

29 W/m

Físico

longitud 2510 mm


ancho 40 mm

altura 100 mm

izquierda

¹ Código RAL ² Foco ³ Lineal
⁴ Valor del producto continente a plena carga (no atenuado)


Distribución luminosa



flood 30° Spot

h (m)	E0° (lx)	ø (m)
1	419	0.54
2	105	1.09
3	47	1.63
4	26	2.17
5	17	2.72

Diseño del producto



Instrucciones de montaje

