



Proyecto / Tipo \_\_\_\_\_

Notas \_\_\_\_\_

Cantidad / Fecha \_\_\_\_\_



General

Pared , Superficie \_\_\_\_\_

negro , RAL9005 <sup>1</sup> \_\_\_\_\_

2920 lm/m \_\_\_\_\_

IP20 \_\_\_\_\_

indirecto 1760 lm \_\_\_\_\_

directa 1760 lm \_\_\_\_\_

total 3520 lm \_\_\_\_\_

LED

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L85 / 50000 h \_\_\_\_\_

seguridad fotobio. RG 0 - sin riesgo \_\_\_\_\_

MacAdam inicial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 89 \_\_\_\_\_

MR 0.61 \_\_\_\_\_

MDER 0.55 \_\_\_\_\_

Óptico

High Performance Opal \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

Eléctrico

non atenuable \_\_\_\_\_

35 W \_\_\_\_\_

CP1 220-240V \_\_\_\_\_

101 lm/W \_\_\_\_\_

29 W/m \_\_\_\_\_

Físico

longitud 1210 mm \_\_\_\_\_

ancho 40 mm \_\_\_\_\_

altura 100 mm \_\_\_\_\_

2.8 kg \_\_\_\_\_


<sup>1</sup> Código RAL

<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

Instrucciones de montaje



Distribución luminosa



Diseño del producto

