

LINEA opal / 2 spots

wall

058-6174D37DH



Proyecto / Tipo _____

Notas _____

Cantidad / Fecha _____



General

Pared , Superficie _____

inclinable máx 89° _____

blanco , RAL9010 ¹ _____

IP20 _____

344 lm _____

LED

3000 K²-tunable white³ _____

CRI ≥ 97²-90³ _____

L95 / 50000 h²-L85 / 50000 h³ _____

seguridad fotobio. RG 0 - sin riesgo _____

MacAdam inicial ≤ 3 SDCM _____

R_g: 92²-99³ , R_f: 86²-90³ , R_(f-15): 94²-88³ _____

MR 0.53 _____

MDER 0.48 _____

2700 K - 5000 K _____

Óptico

Flood _____

ángulo de haz 30° _____

PstLM ≤ 1.0 ⁴ _____

SVM ≤ 0.4 ⁴ _____

High Performance Opal _____

Eléctrico

DALI-2 _____

5.4²-42³ W _____

CP1 220-240V _____

64²-96³ lm/W _____

2²-1³ DALI Addr. _____


Físico

longitud 1410 mm _____

ancho 40 mm _____

altura 100 mm _____


Distribución luminosa



flood 30° Spot

h (m)	E0° (lx)	ø (m)
1	419	0.54
2	105	1.09
3	47	1.63
4	26	2.17
5	17	2.72

Diseño del producto



¹ Código RAL ² Foco ³ Lineal
⁴ Valor del producto continente a plena carga (no atenuado)

Instrucciones de montaje

