

LINEA opal / 1 spot

wall

058-6172538CH



Proyecto / Tipo

Notas

Cantidad / Fecha



General

Pared , Superficie

inclinable máx 89°

negro , RAL9005 ¹

IP20

172 lm

LED

3000 K

CRI ≥ 97²-90³

L95 / 50000 h²-L85 / 50000 h³

seguridad fotobio. RG 0 - sin riesgo

MacAdam inicial ≤ 3 SDCM

R_g: 92²-99³ , R_f: 86²-91³ , R₍₁₋₁₅₎: 94²-89³

MR 0.53²-0.61³

MDER 0.48²-0.55³

Óptico

Flood

ángulo de haz 30°

PstLM ≤ 1.0 ⁴

SVM ≤ 0.4 ⁴

High Performance Opal

Eléctrico

DALI-2

2.7²-17.6³ W

CP1 220-240V

64²-99³ lm/W

1 DALI Addr.

Físico


longitud 710 mm

ancho 40 mm

altura 100 mm


derecha

Distribución luminosa



flood 30°			Spot		
h (m)	E0° (lx)	ø (m)	h (m)	E0° (lx)	ø (m)
1	419	0.54	1	419	0.54
2	105	1.09	2	105	1.09
3	47	1.63	3	47	1.63
4	26	2.17	4	26	2.17
5	17	2.72	5	17	2.72

Diseño del producto



¹ Código RAL ² Foco ³ Lineal
⁴ Valor del producto continente a plena carga (no atenuado)

Instrucciones de montaje

