


LENO microprismatic

semi-recessed / surface system

051-8216637G 051-8920187



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP40	220-240V	☀️	X-PERT
------------------	----------	----	--------

General
Techo / Pared , Superficie ¹ -Semi-empotrado ²
blanco , RAL9010 ³
2010 lm/m
delante IP20 ¹ -IP40 ² , detrás IP20
3680 lm


LED
4000 K
CRI ≥ 80
L90 / 50000 h
seguridad fotobio. RG 0 - sin riesgo
MacAdam inicial ≤ 3 SDCM
MR 0.72
MDER 0.66

Óptico
Microprismatic
UGR < 19
PstLM ≤ 1.0 ⁴
SVM ≤ 0.4 ⁴


Eléctrico
DALI-2
28.6 W
CP1 220-240V
129 lm/W
1 DALI Addr.
16 W/m

Físico
longitud 1830 mm
ancho 89 mm
altura 28 mm
4.3 kg

Distribución luminosa



Diseño del producto



Orificio
longitud 1843 mm
ancho 70 mm
espesor mín. del techo 12.5 mm
profundidad empotrada 13 mm

¹ superficie ² semiempotrado ³ Código RAL
⁴ Valor del producto continente a plena carga (no atenuado)

Instrucciones de montaje

