

LENO microprismatic

semi-recessed / surface system

051-8218637G 051-8920247



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP40	220-240V	☀️	X-PERT
------------------	----------	----	--------

General

Techo / Pared , Superficie ¹ -Semi-empotrado ²
blanco , RAL9010 ³
2010 lm/m
delante IP20 ¹ -IP40 ² , detrás IP20
4910 lm

LED

4000 K
CRI ≥ 80
L90 / 50000 h
seguridad fotobio. RG 0 - sin riesgo
MacAdam inicial ≤ 3 SDCM
MR 0.72
MDER 0.66

Óptico

Microprismatic
UGR < 19
PstLM ≤ 1.0 ⁴
SVM ≤ 0.4 ⁴

Eléctrico

DALI-2
38 W
CP1 220-240V
129 lm/W
1 DALI Addr.
16 W/m

Físico


longitud 2438 mm
ancho 89 mm
altura 28 mm
5.5 kg

Orificio


longitud 2451 mm
ancho 70 mm
espesor mín. del techo 12.5 mm
profundidad empotrada 13 mm

¹ superficie ² semiempotrado ³ Código RAL
⁴ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje

