

TULA micro suspended

canopy surface

049-5715514M 005-2602138



Proyecto / Tipo

Notas

Cantidad / Fecha



General

Techo , Suspendido

chromo

Baldaq  n negro intenso

IP20

746 lm

LED

3000 K

IRC ≥ 90

L90 / 50000 h

MacAdam inicial ≤ 3 SDCM

R_g: 100 , R_f: 90 , R_{f(1-15)}: 87

MR 0.59

MDER 0.54

  ptico

medium

  ngulo de haz 25  

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

El  ctrico

DALI-2

220-240 V

sistema 11.3 W

fijaci  n 8.4 W

fijaci  n 88 lm/W²

18 Vf

500 mA

CP2

F  sico

di  metro 47 mm


altura 500 mm

1.18 kg

¹ Valor del producto continente a plena carga (no atenuado)

² incluida la consideraci  n de las p  rdidas   pticas y las p  rdidas de la unidad de control interna


Distribuci  n luminosa



medium 25  

h (m)	E0 ² (lx)	�� (m)
1	3230	0.44
2	810	0.89
3	360	1.33
4	200	1.78
5	130	2.22

Dise  o del producto



Instrucciones de montaje



Calculadora de iluminaci  n

