

TULA micro suspended

canopy trim

049-5515418M 005-3521018 002-90733



Proyecto / Tipo
Notas
Cantidad / Fecha



General

Techo , Suspendido
negro , RAL9005 ¹
Baldaq�n negro intenso
IP20
648 lm

LED

2700 K
CRI ≥ 90
L90 / 50000 h
MacAdam inicial ≤ 3 SDCM
R _g : 99 , R _r : 91 , R _{t(1-15)} : 89
MR 0.54
MDER 0.49

 ptico

medium
�ngulo de haz 25�
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

El ctrico

DALI-2
11.3 W
CP2 220-240V
57 lm/W

F sico


di�metro 47 mm
altura 300 mm
0.2 kg

Orificio

di�metro 65 mm
espesor m�n. del techo 2 mm
espesor m�x. del techo 25 mm
profundidad empotrada 130 mm

¹ C digo RAL
² Valor del producto continente a plena carga (no atenuado)


Distribuci n luminosa



medium 25 

h (m)	E0� (lx)	� (m)
1	2800	0.44
2	700	0.89
3	310	1.33
4	180	1.78
5	110	2.22

Dise o del producto



Instrucciones de montaje



Calculadora de iluminaci n

