

# TULA nano suspended

canopy trim

049-5510518F 005-3521018 002-90733



Proyecto / Tipo
Notas
Cantidad / Fecha



220-240V
UGR ≤22
cd/m <sup>2</sup> ≤3000
CRI ≥90
X-PERT

## General

Techo , Suspendido
negro , RAL9005 <sup>1</sup>
Baldaqin negro intenso
IP20
717 lm

## LED

3000 K
IRC ≥ 90
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 100 , R <sub>f</sub> : 91 , R <sub>f(1-5)</sub> : 88
MR 0.59
MDER 0.53

## Óptico

flood
beam angle 30°
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Eléctrico

DALI-2
12.1 W
inset 9.1 W
18 Vf
500 mA
CP2 220-240V
59 lm/W
inset 79 lm/W

## Físico

diameter 26 mm
height 300 mm
0.35 kg

## Orificio

diameter 65 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 130 mm



## Distribución luminosa



flood 30°

h (m)	E0° (lx)	ø (m)
1	2110	0.53
2	530	1.07
3	230	1.60
4	130	2.13
5	80	2.66

## Diseño del producto



<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

## Instrucciones de montaje



## Calculadora de iluminación

