

# ARY cable suspended canopy surface

049-521141XM 005-2602138



Proyecto / Tipo \_\_\_\_\_

Notas \_\_\_\_\_

Cantidad / Fecha \_\_\_\_\_



**General**

Techo , Suspendido \_\_\_\_\_

colores especiales \_\_\_\_\_

Baldaqin negro intenso \_\_\_\_\_

IP20 \_\_\_\_\_

642 lm \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

MacAdam inicial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 89 \_\_\_\_\_

MR 0.54 \_\_\_\_\_

MDER 0.49 \_\_\_\_\_

**Óptico**

medium \_\_\_\_\_

ángulo de haz 25° \_\_\_\_\_

**Eléctrico**

DALI-2 \_\_\_\_\_

11.2 W \_\_\_\_\_

CP2 220-240V \_\_\_\_\_

57 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

**Físico**


suspensión 2000 mm con gancho \_\_\_\_\_

diámetro 47 mm \_\_\_\_\_

altura 110 mm \_\_\_\_\_


0.4 kg \_\_\_\_\_

## Distribución luminosa



medium 25°		
h (m)	EO° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

