



SASSO 60/100 round

wall

EN Cylindrical wall surface mounted luminaire made of aluminium, available in 2 sizes; light inset lacquered; housing powder coated; optionally symmetric direct or direct / indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; precise radiation characteristic due to high quality lens system; installation of variant DIRECT optionally for floor or ceiling illumination; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

ES Aplique de pared cilíndrico de aluminio para el montaje en superficie en 2 tamaños; inserto lumin. pintado; carcasa con recubr. de polvo; disponible con proyección simétrica directa o proyección directa/indirecta; iluminación homogénea de la pared o bien del techo mediante distribución uniforme de la luz; proyección precisa con óptica de lente de alta calidad; variante de montaje DIRECT disponible para la iluminación del suelo o el techo; Chip on Board que proporciona una máxima eficiencia; no sombras múltiples; LEDs de eficiencia que proporcionan una alta reproducción cromática

Quickinfo

2700 K, 3000 K, 4000 K
 CRI \geq 90, 2 SDCM
 SASSO 60 up to 69lm/W
 SASSO 100 up to 61lm/W
 L80 @ 50000h
 non DIM, DALI-2

Types




Housing colours



Inset colours



Light distributions



direct and direct/
indirect illumination



high quality
lens



easy
mounting



CRI \geq 95
2 SDCM

Order options

COLOUR TEMPERATURE

| | |
|--------|---|
| 2700 K | 4 |
| 3000 K | 5 |
| 4000 K | 6 |

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

HOUSING COLOUR

| | |
|---|---|
| <input type="radio"/> traffic white RAL 9016 | 7 |
| <input checked="" type="radio"/> jet black RAL 9005 | 1 |

INSET COLOUR

| | |
|---|---|
| <input type="radio"/> traffic white RAL 9016 (UGR _{≤22}) | 7 |
| <input type="radio"/> matt silver (UGR _{≤19}) | 4 |
| <input checked="" type="radio"/> jet black RAL 9005 (UGR _{≤16}) | 1 |
| <input type="radio"/> gold dust RAL 260-M (UGR _{≤19}) | 9 |

BEAM ANGLE

opal lens

Options on request

COLOUR RENDERING INDEX

CRI ≥ 95, 2 SDCM



SASSO 60 round wall



DIRECT

| SYSTEM POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|--------------|--------------|---------------|------------------------------|
| 11.7 W | 2700 K | 647 lm | 0 4 8 - 3 1 5 0 :: ◆ ◆ ■ ■ ○ |
| | 3000 K | 683 lm | |
| | 4000 K | 724 lm | |

DIRECT / INDIRECT

| SYSTEM POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|--------------|--------------|---------------|------------------------------|
| 20.4 W | 2700 K | 2 × 643 lm | 0 4 8 - 3 1 6 0 :: ◆ ◆ ■ ■ ○ |
| | 3000 K | 2 × 678 lm | |
| | 4000 K | 2 × 720 lm | |

SASSO 100 round wall



DIRECT

| SYSTEM POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|--------------|--------------|---------------|------------------------------|
| 20.4 W | 2700 K | 1130 lm | 0 4 8 - 3 4 5 0 :: ◆ ◆ ■ ■ ○ |
| | 3000 K | 1180 lm | |
| | 4000 K | 1240 lm | |

DIRECT / INDIRECT

| SYSTEM POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|--------------|--------------|---------------|------------------------------|
| 41 W | 2700 K | 2 × 1130 lm | 0 4 8 - 3 4 6 0 :: ◆ ◆ ■ ■ ○ |
| | 3000 K | 2 × 1180 lm | |
| | 4000 K | 2 × 1240 lm | |