

# SASSO 100 round adjustable

semi-recessed

048-34014177S 002-90779



Proyecto / Tipo
Notas
Cantidad / Fecha



220-240V
X-PERT
X-PERT

<b>General</b>
Techo , Semi-empotrado
inclinable máx 20°
rotación 360°
blanco , RAL9016/white <sup>1</sup>
Color interno blanco
IP20
1420 lm

<b>LED</b>
2700 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>r</sub> : 91 , R <sub>t(1-15)</sub> : 89
MR 0.53
MDER 0.48

<b>Óptico</b>
spot
ángulo de haz 19°
UGR < 19
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>


<b>Eléctrico</b>
DALI-2
20.2 W
CP2 220-240V
70 lm/W
1 DALI Addr.

<b>Físico</b>
diámetro 100 mm
altura 115 mm
0.13 kg

<b>Orificio</b>
profundidad empotrada 100 mm

<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

