

SASSO 100 square adjustable

trim

048-2730419S 048-279731G 002-90777



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP40	220-240V	↺	X-PERT	X-PERT
------------------	----------	---	--------	--------

General

Techo , Empotrado
inclinable máx 30°
dorado , RAL260-M ¹
Set de montaje plateado-gris
delante IP40 , detrás IP20
1350 lm

LED

2700 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89
MR 0.53
MDER 0.48

Óptico

spot
ángulo de haz 18°
UGR < 13 , ≥65° <3000 cd/m ²
P _{stLM} ≤ 1.0 ²
SVM ≤ 0.4 ²

Eléctrico

non atenuable
20.2 W
CP2 220-240V
67 lm/W

Físico


borde
longitud 118 mm
ancho 118 mm
altura 95 mm
0.5 kg

Orificio


longitud 112 mm
ancho 112 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 100 mm

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

