

SASSO 100 round adjustable

trimless

048-2720614W 048-2796117 002-90779



Proyecto / Tipo	
Notas	
Cantidad / Fecha	



↑ IP20 ↓ IP40	220-240V	360°	X-PERT	X-PERT
------------------	----------	------	--------	--------

General

Techo , Empotrado
inclinable máx 30°
rotación 360°
plata mate
delante IP40 , detrás IP20
1830 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 97 , R _f : 90 , R ₍₁₋₅₎ : 89
MR 0.81
MDER 0.74

Óptico

wide flood
ángulo de haz 60°
≥65° <3000 cd/m ²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

DALI-2
20.2 W
CP2 220-240V
91 lm/W
1 DALI Addr.

Físico


sin borde
diámetro 105 mm
altura 95 mm
0.56 kg

Orificio


diámetro 106 mm
espesor mín. del techo 12.5 mm
espesor máx. del techo 25 mm
profundidad empotrada 100 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

