

# SASSO 100 round adjustable

trimless

048-2720514W 048-2796117 002-90776



Proyecto / Tipo	
Notas	
Cantidad / Fecha	



↑ IP20 ↓ IP40	220-240V	360°	X-PERT	X-PERT
------------------	----------	------	--------	--------

## General

Techo , Empotrado
inclinable máx 30°
rotación 360°
plata mate
delante IP40 , detrás IP20
2270 lm

## LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 100 , R <sub>f</sub> : 91 , R <sub>f1-5</sub> : 88
MR 0.59
MDER 0.53

## Óptico

wide flood
ángulo de haz 60°
≥65° <3000 cd/m <sup>2</sup>
PstLM ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

## Eléctrico

DALI-2
29.2 W
CP2 220-240V
78 lm/W
1 DALI Addr.

## Físico


sin borde
diámetro 105 mm
altura 95 mm
0.55 kg

## Orificio


diámetro 106 mm
espesor mín. del techo 12.5 mm
espesor máx. del techo 25 mm
profundidad empotrada 100 mm

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

