

SASSO 100 square downlight

trimless

048-2710611S 048-2797117 002-90776



| |
|------------------|
| Proyecto / Tipo |
| Notas |
| Cantidad / Fecha |



| | | | |
|------------------|----------|--------|--------|
| ↑ IP20 ↓ IP44 | 220-240V | X-PERT | X-PERT |
|------------------|----------|--------|--------|

General

| |
|-------------------------------|
| Techo , Empotrado |
| negro , RAL9005 ¹ |
| Set de montaje blanco tráfico |
| delante IP44 , detrás IP20 |
| 1990 lm |

LED

| |
|---|
| 4000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| MacAdam inicial ≤ 2 SDCM |
| R _g : 97 , R _f : 90 , R _{t(1-15)} : 89 |
| MR 0.81 |
| MDER 0.74 |

Óptico

| |
|---|
| spot |
| ángulo de haz 19° |
| UGR < 13 , ≥ 65° < 3000 cd/m ² |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Eléctrico

| |
|--------------|
| DALI-2 |
| 29.2 W |
| CP2 220-240V |
| 68 lm/W |
| 1 DALI Addr. |

Físico


| |
|-----------------|
| sin borde |
| longitud 105 mm |
| ancho 105 mm |
| altura 75 mm |
| 0.51 kg |

Orificio

| |
|--------------------------------|
| longitud 106 mm |
| ancho 106 mm |
| espesor mín. del techo 12.5 mm |
| espesor máx. del techo 25 mm |
| profundidad empotrada 80 mm |

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

