

SASSO 100 square downlight

trim

048-2710519W 048-2797317 002-90776



| |
|------------------|
| Proyecto / Tipo |
| Notas |
| Cantidad / Fecha |



| | | | |
|------------------|----------|--------|--------|
| ↑ IP20 ↓ IP44 | 220-240V | X-PERT | X-PERT |
|------------------|----------|--------|--------|

General

| |
|--------------------------------|
| Techo , Empotrado |
| dorado , RAL260-M ¹ |
| Set de montaje blanco tráfico |
| delante IP44 , detrás IP20 |
| 2270 lm |

LED

| |
|--|
| 3000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| MacAdam inicial ≤ 2 SDCM |
| R _g : 100 , R _f : 91 , R _{f(1-15)} : 88 |
| MR 0.59 |
| MDER 0.53 |

Óptico

| |
|------------------------------|
| wide flood |
| ángulo de haz 65° |
| ≥65° <1500 cd/m ² |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Eléctrico

| |
|--------------|
| DALI-2 |
| 29.2 W |
| CP2 220-240V |
| 78 lm/W |
| 1 DALI Addr. |

Físico


| |
|-----------------|
| borde |
| longitud 118 mm |
| ancho 118 mm |
| altura 75 mm |
| 0.52 kg |

Orificio


| |
|------------------------------|
| longitud 112 mm |
| ancho 112 mm |
| espesor mín. del techo 2 mm |
| espesor máx. del techo 25 mm |
| profundidad empotrada 80 mm |

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

