

SASSO 100 square downlight

trim

048-2710611M 048-2797317 002-90777



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

General

Techo , Empotrado
negro , RAL9005 ¹
Set de montaje blanco tráfico
delante IP44 , detrás IP20
1510 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 97 , R _f : 90 , R _{t(1-15)} : 89
MR 0.81
MDER 0.74

Óptico

medium
ángulo de haz 33°x34°
UGR < 13 , ≥65° <1500 cd/m ²
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Eléctrico

non atenuable
20.2 W
CP2 220-240V
75 lm/W

Físico


borde
longitud 118 mm
ancho 118 mm
altura 75 mm
0.5 kg

Orificio

longitud 112 mm
ancho 112 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 80 mm

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

