

# SASSO 100 square downlight

trim

048-2710511F 048-2797317 002-90776



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

## General

Techo , Empotrado
negro , RAL9005 <sup>1</sup>
Set de montaje blanco tráfico
delante IP44 , detrás IP20
2120 lm

## LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 100 , R <sub>f</sub> : 91 , R <sub>f(1-15)</sub> : 88
MR 0.59
MDER 0.53

## Óptico

flood
ángulo de haz 45°
UGR < 16 , ≥65° <3000 cd/m²
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Eléctrico

DALI-2
29.2 W
CP2 220-240V
73 lm/W
1 DALI Addr.


## Físico

borde
longitud 118 mm
ancho 118 mm
altura 75 mm
0.52 kg


## Orificio

longitud 112 mm
ancho 112 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 80 mm

## Distribución luminosa



## Diseño del producto



<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

## Instrucciones de montaje



## Calculadora de iluminación

