

SASSO 100 round downlight

trim

048-2700519W 048-279631G 002-90774



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

General

Techo , Empotrado
dorado , RAL260-M ¹
Set de montaje plateado-gris
delante IP44 , detrás IP20
2210 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{f(1-15)} : 88
MR 0.59
MDER 0.53

Óptico

wide flood
ángulo de haz 66°
≥65° <1500 cd/m ²
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Eléctrico

non atenuable
29.2 W
inserto 24.8 W
36 Vf
700 mA
CP2 220-240V
76 lm/W

Físico

borde
diámetro 118 mm
altura 75 mm
0.45 kg


Orificio

diámetro 108 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 80 mm

¹ Código RAL

² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

