

# SASSO 100 round downlight

trim

048-2700519S 048-2796317 002-90776



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

## General

Techo , Empotrado
dorado , RAL260-M <sup>1</sup>
Set de montaje blanco tráfico
delante IP44 , detrás IP20
1910 lm

## LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 100 , R <sub>f</sub> : 91 , R <sub>(f-15)</sub> : 88
MR 0.59
MDER 0.53

## Óptico

spot
ángulo de haz 19°
UGR < 13 , ≥ 65° < 3000 cd/m <sup>2</sup>
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Eléctrico

DALI-2
29.2 W
inserto 24.8 W
36 Vf
700 mA
CP2 220-240V
65 lm/W
1 DALI Addr.

## Físico

borde
diámetro 118 mm
altura 75 mm
0.49 kg


## Orificio

diámetro 108 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 80 mm


<sup>1</sup> Código RAL

<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

