

# SASSO 100 round downlight

trim

048-2700614F 048-2796317 002-90777



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

## General

Techo , Empotrado
plata mate
Set de montaje blanco tráfico
delante IP44 , detrás IP20
1750 lm

## LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 97 , R <sub>f</sub> : 90 , R <sub>t(1-15)</sub> : 89
MR 0.81
MDER 0.74

## Óptico

flood
ángulo de haz 44°
UGR < 16 , ≥65° <3000 cd/m²
PstLM ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

## Eléctrico

non atenuable
20.2 W
inserto 17.2 W
36 Vf
500 mA
CP2 220-240V
87 lm/W

## Físico


borde
diámetro 118 mm
altura 75 mm
0.47 kg

## Orificio

diámetro 108 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 80 mm

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

