

SASSO 100 round downlight

trim

048-2700514S 048-279631G 002-90774



| |
|------------------|
| Proyecto / Tipo |
| Notas |
| Cantidad / Fecha |



General

| |
|------------------------------|
| Techo , Empotrado |
| plata mate |
| Set de montaje plateado-gris |
| delante IP44 , detrás IP20 |
| 1940 lm |

LED

| |
|--|
| 3000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| MacAdam inicial ≤ 2 SDCM |
| R _g : 100 , R _f : 91 , R _{f(1-15)} : 88 |
| MR 0.59 |
| MDER 0.53 |

Óptico

| |
|---|
| spot |
| ángulo de haz 19° |
| UGR < 13 , $\geq 65^\circ$ < 3000 cd/m ² |
| PstLM ≤ 1.0 ¹ |
| SVM ≤ 0.4 ¹ |

Eléctrico

| |
|----------------|
| non atenuable |
| 29.2 W |
| inserto 24.8 W |
| 36 Vf |
| 700 mA |
| CP2 220-240V |
| 66 lm/W |

Físico


| |
|-----------------|
| borde |
| diámetro 118 mm |
| altura 75 mm |
| 0.45 kg |

Orificio

| |
|------------------------------|
| diámetro 108 mm |
| espesor mín. del techo 2 mm |
| espesor máx. del techo 25 mm |
| profundidad empotrada 80 mm |

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

