



SASSO 60 round sensor/emergency

recessed

EN Round inset (Emergency Light or Sensor); installation without tools in mounting set (trimless or with trim); surface lacquered; installation possible in different housings; LED emergency light inset: 3 variants with different test possibilities - Basic with test button, selftest with status LED or Pro DALI with monitoring via DALI; sensor with DALI-2 control: 2 variants - Basic with brightness and presence sensor or Pro with additional temperature, humidity, air quality and noise level measurement



ES Inserto redondo (luz emergencia/sensor); instalación sin herramientas mediante kit de montaje (con o sin marco); superficie lacada; posibilidad de instalar distintas carcasa; inserto luz de emerg. LED: 3 variantes con difer. opciones de test - Basic con botón de prueba, autotest con LED de estado o Pro DALI con superv. a través de DALI; sensor con control DALI-2: 2 variantes - Basic con sensor de luminosidad y presencia o Pro con medi. adic. de temperatura, humedad y calidad del aire y nivel de ruido

Quickinfo

sensor
ESSENTIAL, SENSE
DALI-2

emergency light
6500K
CRI ≥ 80
200lm
L80 @ 50000h
non maintained

Types



Housing colours



Inset colours



Sensors



essen- sense
tial

Order options

INSET COLOUR

<input type="checkbox"/> traffic white RAL 9016	7
<input checked="" type="checkbox"/> jet black RAL 9005	1

BEAM ANGLE EMERGENCY LIGHT

spot lens	
escape route lens	
anti panic lens	


Options on request

MOUNTING SET

acoustic soft ceilings	
------------------------	--

INSET COLOUR

grey, gold	
------------	--



SASSO 60 sensor round



ESSENTIAL SENSOR

TYPE	
brightness & presence	

ORDER CODE	0 4 8 - 2 6 9 3 1 1
------------	---------------------




SENSE SENSOR

TYPE	
brightness, presence, temperature, sound pressure, humidity, CO ₂	

ORDER CODE	0 4 8 - 2 6 9 3 1 2
------------	---------------------

SASSO 60 emergency light round




EMERGENCY 3h

TYPE	
BASIC 2W	
SELF-TEST 2W	
PRO DALI 2W	


ORDER CODE	0 4 8 - 2 6 9 3 2 1
0 4 8 - 2 6 9 3 2 2	
0 4 8 - 2 6 9 3 2 3	

incl. 3 interchangeable lenses


Light distributions






emergency light
spot lens



emergency light
escape route lens



emergency light
anti panic lens



Mounting accessories

TRIMLESS MOUNTING SET

for plasterboard ceilings 12.5/15/25 mm	ORDER CODE
○ traffic white RAL9016	0 4 8 - 2 6 9 6 1 1 7

MOUNTING SET WITH TRIM

TYPE	COLOUR	ORDER CODE
1 lamp	○ traffic white RAL9016	0 4 8 - 2 6 9 6 3 1 7
	● jet black RAL 9005	0 4 8 - 2 6 9 6 3 1 8
2 lamps	○ traffic white RAL9016	0 4 8 - 2 6 9 8 3 1 7
	● jet black RAL 9005	0 4 8 - 2 6 9 8 3 1 8

CONCRETE MOUNTING HOUSING

COLOUR	L-W-H (mm)	ORDER CODE
exposed concrete ceilings	230x230x162	0 4 8 - 2 6 9 5 2 1 0
primed concrete ceilings*	614x307x120	0 4 8 - 2 6 9 5 1 1 0

*order mounting set separately, not applicable for 2 lamps mounting set with trim