

SASSO 60 square downlight

trim 2 lamps

048-2612E14M 048-2699318 002-90762



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP40	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

General

Techo , Empotrado
plata mate
Set de montaje negro intenso
delante IP40 , detrás IP20
1630 lm

LED

colour warm dimming
1800 K - 3000 K
CRI ≥ 90
L85 / 50000 h
MacAdam inicial ≤ 3 SDCM
R _g : 101 , R _r : 94 , R _{t(1-5)} : 96
MR 0.64
MDER 0.58

Óptico

medium
ángulo de haz 26°
UGR < 19
P _{stLM} ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

DALI-2
24.0 W
total de insertos 20.4 W
CP2 220-240V
68 lm/W
1 DALI Addr.

Físico


borde
longitud 147 mm
ancho 81 mm
altura 48 mm
0.34 kg

Orificio

longitud 138 mm
ancho 73 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 100 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

