

# SASSO 60 square downlight

trim 2 lamps

048-2612E11M 048-269931G 002-90762



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP40	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

## General

Techo , Empotrado
negro , RAL9005 <sup>1</sup>
Set de montaje plateado-gris
delante IP40 , detrás IP20
1450 lm

## LED

colour warm dimming
1800 K - 3000 K
CRI ≥ 90
L85 / 50000 h
MacAdam inicial ≤ 3 SDCM
R <sub>g</sub> : 101 , R <sub>r</sub> : 94 , R <sub>t(1-5)</sub> : 96
MR 0.64
MDER 0.58

## Óptico

medium
ángulo de haz 26°
UGR < 19
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Eléctrico

DALI-2
24.0 W
total de insertos 20.4 W
CP2 220-240V
60 lm/W
1 DALI Addr.

## Físico


borde
longitud 147 mm
ancho 81 mm
altura 48 mm
0.34 kg

## Orificio

longitud 138 mm
ancho 73 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 100 mm

<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

