

# SASSO 60 square downlight

trim

048-2612519M 048-269731G 002-90762



|                  |
|------------------|
| Proyecto / Tipo  |
| Notas            |
| Cantidad / Fecha |



|                  |          |        |        |
|------------------|----------|--------|--------|
| ↑ IP20<br>↓ IP44 | 220-240V | X-PERT | X-PERT |
|------------------|----------|--------|--------|

## General

|                                |
|--------------------------------|
| Techo , Empotrado              |
| dorado , RAL260-M <sup>1</sup> |
| Set de montaje plateado-gris   |
| delante IP44 , detrás IP20     |
| 955 lm                         |

## LED

|  |
|--|
| 3000 K   |
| CRI ≥ 90   |
| L80 / 50000 h  |
| MacAdam inicial ≤ 2 SDCM   |
| R <sub>g</sub> : 100 , R <sub>f</sub> : 91 , R <sub>f(1-15)</sub> : 88 |
| MR 0.59  |
| MDER 0.53  |

## Óptico

|   |
|---|
| medium                                  |
| ángulo de haz 21°                       |
| UGR < 16 , ≥65° <3000 cd/m <sup>2</sup> |
| PstLM ≤ 1.0 <sup>2</sup>                |
| SVM ≤ 0.4 <sup>2</sup>                  |

## Eléctrico

|              |
|--------------|
| DALI-2       |
| 12.6 W       |
| CP2 220-240V |
| 76 lm/W      |
| 1 DALI Addr. |

## Físico


|                |
|----------------|
| borde          |
| longitud 80 mm |
| ancho 80 mm    |
| altura 48 mm   |
| 0.29 kg        |

## Orificio

|                              |
|------------------------------|
| longitud 73 mm               |
| ancho 73 mm                  |
| espesor mín. del techo 2 mm  |
| espesor máx. del techo 25 mm |
| profundidad empotrada 100 mm |

<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

