

SASSO 60 square downlight

trim 2 lamps

048-2612411M 048-269931G 002-90762



Proyecto / Tipo

Notas

Cantidad / Fecha



General

Techo , Empotrado

negro , RAL9005 ¹

Set de montaje plateado-gris

delante IP44 , detrás IP20

1730 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

MacAdam inicial ≤ 2 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.53

MDER 0.48

Óptico

medium

ángulo de haz 21°

UGR < 13 , $\geq 65^\circ$ <1500 cd/m²

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Eléctrico

DALI-2

25.2 W

total de insertos 21.4 W

CP2 220-240V

69 lm/W

1 DALI Addr.

Físico

borde

longitud 147 mm

ancho 81 mm

altura 48 mm

0.34 kg

Orificio

longitud 138 mm

ancho 73 mm

espesor mín. del techo 2 mm


espesor máx. del techo 25 mm

profundidad empotrada 100 mm

¹ Código RAL

² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto

