

# SASSO 60 round downlight

trim 2 lamps

048-2602614F 048-2698318 002-90762



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	360°	X-PERT	X-PERT
------------------	----------	------	--------	--------

## General

Techo , Empotrado
rotación 360°
plata mate
Set de montaje negro intenso
delante IP44 , detrás IP20
2220 lm

## LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 97 , R <sub>f</sub> : 90 , R <sub>(1-15)</sub> : 89
MR 0.81
MDER 0.74

## Óptico

flood
ángulo de haz 42°
UGR < 19 , ≥65° <1500 cd/m²
PstLM ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

## Eléctrico

DALI-2
25.2 W
total de insertos 21.4 W
CP2 220-240V
88 lm/W
1 DALI Addr.

## Físico


borde
longitud 147 mm
ancho 80 mm
altura 48 mm
0.34 kg

## Orificio


diámetro 70 mm
longitud 136 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 110 mm

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

