

SASSO 60 round downlight

trim

048-2602617M 048-269631G 002-90762



| |
|------------------|
| Proyecto / Tipo |
| Notas |
| Cantidad / Fecha |



| | | | | |
|------------------|----------|------|--------|--------|
| ↑ IP20 ↓ IP44 | 220-240V | 360° | X-PERT | X-PERT |
|------------------|----------|------|--------|--------|

General

| |
|-------------------------------|
| Techo , Empotrado |
| rotación 360° |
| blanco , RAL9016 ¹ |
| Set de montaje plateado-gris |
| delante IP44 , detrás IP20 |
| 1050 lm |

LED

| |
|---|
| 4000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| MacAdam inicial ≤ 2 SDCM |
| R _g : 97 , R _f : 90 , R ₍₁₋₅₎ : 89 |
| MR 0.81 |
| MDER 0.74 |

Óptico

| |
|--------------------------------------|
| medium |
| ángulo de haz 22° |
| UGR < 19 |
| P _{stLM} ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Eléctrico

| |
|--------------|
| DALI-2 |
| 12.6 W |
| CP2 220-240V |
| 83 lm/W |
| 1 DALI Addr. |

Físico


| |
|----------------|
| borde |
| diámetro 80 mm |
| altura 48 mm |
| 0.27 kg |

Orificio

| |
|------------------------------|
| diámetro 73 mm |
| espesor mín. del techo 2 mm |
| espesor máx. del techo 25 mm |
| profundidad empotrada 110 mm |

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

