

# SASSO 60 round downlight

trim

048-2602617M 048-2696318 002-90762



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	360°	X-PERT	X-PERT
------------------	----------	------	--------	--------

## General

Techo , Empotrado
rotación 360°
blanco , RAL9016 <sup>1</sup>
Set de montaje negro intenso
delante IP44 , detrás IP20
1050 lm

## LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 97 , R <sub>f</sub> : 90 , R <sub>(1-5)</sub> : 89
MR 0.81
MDER 0.74

## Óptico

medium
ángulo de haz 22°
UGR < 19
P <sub>stLM</sub> ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Eléctrico

DALI-2
12.6 W
CP2 220-240V
83 lm/W
1 DALI Addr.

## Físico


borde
diámetro 80 mm
altura 48 mm
0.27 kg

## Orificio

diámetro 73 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 110 mm

<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

