

# SASSO 60 round downlight

trimless

048-2602517F 048-2696117 002-90762



Proyecto / Tipo	
Notas	
Cantidad / Fecha	



↑ IP20 ↓ IP44	220-240V	360°	X-PERT	X-PERT
------------------	----------	------	--------	--------

## General

Techo , Empotrado
rotación 360°
blanco , RAL9016 <sup>1</sup>
Set de montaje blanco tráfico
delante IP44 , detrás IP20
1030 lm

## LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 100 , R <sub>f</sub> : 91 , R <sub>f1-5</sub> : 88
MR 0.59
MDER 0.53

## Óptico

flood
ángulo de haz 46°
UGR < 19 , ≥65° <1500 cd/m <sup>2</sup>
P <sub>st</sub> LM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Eléctrico

DALI-2
12.6 W
CP2 220-240V
82 lm/W

## Físico


sin borde
diámetro 73 mm
altura 48 mm
0.28 kg

## Orificio


diámetro 73 mm
profundidad empotrada 120 mm

<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

