

# SASSO 60 round downlight

trim

048-2602414M 048-2696318 002-90771



|                  |
|------------------|
| Proyecto / Tipo  |
| Notas            |
| Cantidad / Fecha |



|                  |          |      |        |        |
|------------------|----------|------|--------|--------|
| ↑ IP20<br>↓ IP44 | 220-240V | 360° | X-PERT | X-PERT |
|------------------|----------|------|--------|--------|

## General

|                              |
|------------------------------|
| Techo , Empotrado            |
| rotación 360°                |
| plata mate                   |
| Set de montaje negro intenso |
| delante IP44 , detrás IP20   |
| 948 lm                       |

## LED

|  |
|--|
| 2700 K   |
| CRI ≥ 90   |
| L80 / 50000 h  |
| MacAdam inicial ≤ 2 SDCM   |
| R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 89 |
| MR 0.53  |
| MDER 0.48  |

## Óptico

|                               |
|-------------------------------|
| medium                        |
| ángulo de haz 21°             |
| UGR < 16 , ≥ 65° < 1500 cd/m² |
| PstLM ≤ 1.0 <sup>1</sup>      |
| SVM ≤ 0.4 <sup>1</sup>        |

## Eléctrico

|               |
|---------------|
| non atenuable |
| 12.6 W        |
| CP2 220-240V  |
| 75 lm/W       |


## Físico

|                |
|----------------|
| borde          |
| diámetro 80 mm |
| altura 48 mm   |
| 0.21 kg        |

## Orificio

|                              |
|------------------------------|
| diámetro 73 mm               |
| espesor mín. del techo 2 mm  |
| espesor máx. del techo 25 mm |
| profundidad empotrada 60 mm  |

## Distribución luminosa



## Diseño del producto



<sup>1</sup> Valor del producto continente a plena carga (no atenuado)

## Instrucciones de montaje



## Calculadora de iluminación

